

Ex-Pack

REPLACES:

2D Fitting, Exterior wall lights, etc.




OPERATING

TEMP:
-20°C - 45°C

SUITABLE FOR:

Offices, warehouses, car parks, external lighting

COLOUR TEMPERATURE:

 DAYLIGHT 5.5-6K
 NATURAL 4-4.5K
 WARM 2.7-3K

The ExPack is an incredible alternative for exterior wall mounted solutions at height. Starting at 60W output and going up to 120W, it gives a snug fit offering instead of having to use mounted floods or street light fittings.

It delivers a up to 140lm/W in a vandal-proof Die-Cast Aluminium body, with a Polycarbonate lens. Each layer of the fitting is fully maintainable and replaceable. In the event of a failure, it means the fitting is quickly repaired and extremely environmentally friendly.

5 YEAR
GUARANTEE



LAMP SPECIFICATION:

VOLTAGE AC.....220V - 240V
 FREQUENCY.....50HZ - 60HZ
 OP TEMP.....- 20°C - 45°C
 CRI.....>80
 POWER FACTOR.....>0.95
 IP RATING.....IP65
 BEAM ANGLE.....120°
 LIFESPAN.....50,000 Hours



50,000 HOURS



INSTANT ON



ZERO UV



NO HARMFUL GASES



SMD LED'S



FLICKER FREE

WATTAGE	WEIGHT	PRODUCT CODE	COLOUR TEMP	LUMENS
60W	2.6kg	LBVWP60D	DAYLIGHT (5.7-6K)	8400
		LBVWP60N	NATURAL (4.5-5K)	8190
		LBVWP60W	WARM (3-3.5K)	7980
100W	3.1kg	LBVWP100D	DAYLIGHT (5.7-6K)	14000
		LBVWP100N	NATURAL (4.5-5K)	13650
		LBVWP100W	WARM (3-3.5K)	13300
120W	3.7kg	LBVWP120D	DAYLIGHT (5.7-6K)	16800
		LBVWP120N	NATURAL (4.5-5K)	16380
		LBVWP120W	WARM (3-3.5K)	15960

COMPLIES WITH:

EMC Directive 2004/108/EC, (EN55015:2006+A2:2009, EN61547:2009, EN61000-3-2:2006+A1:2009, EN61000-3-3:2008)
LVD DIRECTIVE 2006/95/EV (EN60598-1:2008+A11:2009, EN60598-2-1:1989)

